






HSF



RECOMMENDED PCB LAYOUT
(Tolerance: ±0.05)

SPECIFICATION:

Current Rating: 1Amp
 Insulation Resistance: 1000MΩ min
 Contact Resistance: 20MΩ max
 Withstand Voltage: 500V AC/DC
 Operating Temperature: -40° C to +105° C
 Contact Material: Brass
 Contact Plating: Au or Sn Over Ni
 Insulator Material: PA6T+30%GF UL 94V-0


Ordering Code:

BHAM04 - X - X - X - X - X - X
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No:
 ② No. of Contacts
 06 08 10 14 16
 20 24 26 30 32
 34 40 44 50 60
 64 80 100
 ③ Contact Plating:
 G0:Gold flash S0:Selective
 G1:3U" Gold S1:Selective 3u"
 G2:5u" Gold S2:Selective 5u"
 G3:10u" Gold S3:Selective 10u"
 G4:15u" Gold S4:Selective 15u"
 G5:30u" Gold S5:Selective 30u"
 SN:Tin
 ④ Color Insulator
 B:Black
 U:Blue
 W:White
 ⑤ Insulator Material
 B:PA6T
 C:LCP
 E:PA9T
 ⑥ Plastic body height:
 H1: 8.20 H2:9.50
 H3:10.20 H4:11.50
 H5:12.10 H6:15.30
 H7:16.60
 ⑦ Packing
 A:Tray
 B:Bag
 T:Tube
 U:Tube+CAP
 R:Tape&Reel
 W:Tape&Reel+CAP

Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW YG ZHONG DATE 01/05/2016
 CHECK BobYang DATE 01/05/2016



3rd ANGLE PROJECTION

AntenK® ANTENK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE: 1.27mm Box Header SMT With
 post, High Profile

DRAWING NO: BHAM04-XXXXXXX

PRODUCT NO: BHAM04-XXXXXXX

REV

DESCRIPTION

DATE

1

2

3

4

5

6

7

8