


SOT-23**Marking: 2D****SOT-23 贴片塑封三极管****SOT-23 Plastic-Encapsulate Transistors****特征 Features**

- 与 MMBTA42 配对; Complementary to MMBTA42
- 最大功率耗散 300mW; Power Dissipation of 300mW
- 高稳定性和可靠性。High Stability and High Reliability

机械数据 Mechanical Data

- 封装: SOT-23 封装 SOT-23 Small Outline Plastic Package
- 环氧树脂 UL 易燃等级 Epoxy UL: 94V-0
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性(TA = 25°C 除非另有规定)

Maximum Ratings & Thermal Characteristics (Ratings at 25°C ambient temperature unless otherwise specified.)

参数 Parameters	符号 Symbol	数值 Value	单位 Unit
Collector-Base Voltage	V _{CBO}	-300	V
Collector-Emitter Voltage	V _{CEO}	-300	V
Emitter -Base Voltage	V _{EBO}	-5	V
Collector Current-Continuous	I _C	-200	mA
Collector Power Dissipation	P _C	300	mW
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-55-+150	°C
Thermal resistance From junction to ambient	R _{θJA}	417	°C/W







电特性 (TA = 25°C 除非另有规定)

Electrical Characteristics (Ratings at 25°C ambient temperature unless otherwise specified).


参数 Parameter	符号 Symbols	测试条件 Test Condition	界限 Limits		单位 Unit
			Min	Max	
Collector-base breakdown voltage	V(BR)CBO	I _C =-100μA, I _E =0	-300		V
Collector-emitter breakdown voltage	V(BR)CEO *	I _C =-1mA, I _B =0	-300		V
Emitter-base breakdown voltage	V(BR)EBO	I _E =-100μA, I _C =0	-5		V
Collector cut-off current	I _{CBO}	V _{CB} =-200V, I _E =0		-250	nA
Emitter cut-off current	I _{EBO}	V _{EB} =-5V, I _C =0		-100	nA
DC current gain	hFE(1) *	V _{CE} =-10V, I _C =-1mA	60		
	hFE(2) *	V _{CE} =-10V, I _C =-10mA	100	200	
	hFE(3) *	V _{CE} =-10V, I _C =-30mA	60		
Collector-emitter saturation voltage	V _{CE(sat)} *	I _C =-20mA, I _B =-2mA		-0.2	V
Base -emitter saturation voltage	V _{BE(sat)} *	I _C =-20mA, I _B =-2mA		-0.9	V
Transition frequency	f _T	V _{CE} =-20V, I _C =10mA, f=30MHz	50		MHz

*Pulse test: pulse width ≤ 300μs, duty cycle ≤ 2.0%


Typical characteristics



MMBTA92



SOT-23 PACKAGE OUTLINE Plastic surface mounted package



焊盘设计参考Precautions: PCB Design
Recommended land dimensions for SOT-23 diode. Electrode patterns for PCBs

