



ATTENTION
OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
SENSITIVE
DEVICES



CAUTION

This bag contains
MOISTURE-SENSITIVE DEVICES

LEVEL

3

If blank, see adjacent
bar code label

1. Calculated shelf life in sealed bag: 12 months at $<40^{\circ}\text{C}$ and $<90\%$ relative humidity (RH)
 2. Peak package body temperature: 260°C
If blank, see adjacent bar code label
 3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must
a) Mounted within: 168 hours of factory
If blank, see adjacent bar code label
conditions $\leq 30^{\circ}\text{C}/60\%$
b) Stored at $<10\%\text{RH}$
 4. Devices require bake, before mounting, if:
a) Humidity Indicator Card is $>10\%$ when read at $23\pm 5^{\circ}\text{C}$
b) 3a or 3b not met
 5. If baking is required, devices may be baked for 48 hours at $125\pm 5^{\circ}\text{C}$
Note: If device containers cannot be subjected to high temperature or shorter bake times are desired, reference IPC/JEDEC J-STD-033 for bake procedure
- Bag Seal Date: _____
If blank, see adjacent bar code label
- Note: Level and body temperature defined by IPC/JEDEC J-STD-020



平芯微

Wuxi PWCHIP Semi Technology CO., LTD

Product: PW2312

Lot No:

D/C: 2350

QTY: 3000

Date:
2023/12/08



ROHS



无锡市平芯微半导体科技有限公司
www.pwchip.com