



ATTENTION
OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
SENSITIVE
DEVICES



CAUTION

This bag contains
MOISTURE-SENSITIVE DEVICES

LEVEL

3

1. Calculated shelf life in sealed bag: 12 months at $< 40^{\circ}\text{C}$ and $< 90\%$ relative humidity (RH)
 2. Peak package body temperature: 260 $^{\circ}\text{C}$
If blank, see adjacent bar code label
 3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must
a) Mounted within: 168 hours of factory
If blank, see adjacent bar code label
conditions $\leq 30^{\circ}\text{C}/60\%$
b) Stored at $< 10\%$ RH
 4. Devices require bake, before mounting, if:
a) Humidity Indicator Card is $> 10\%$ when read at $23 \pm 5^{\circ}\text{C}$
b) 3a or 3b not met
 5. If baking is required, devices may be baked for 48 hours at $125 \pm 5^{\circ}\text{C}$
Note: If device containers cannot be subjected to high temperature or shorter bake times are desired.
reference IPC/JEDEC J-STD-033 for bake procedure
- Bag Seal Date: _____
If blank, see adjacent bar code label
- Note: Level and body temperature defined by IPC/JEDEC J-STD-020

夸克微科技



PULAN TECHNOLOGY CO., LIMITED

Device Name : PL2628



Quantity : 3000EA



Data Code : 2319



Lot No

夸克微科技



【公司网站】

PL20230505

AMAU0EH12ZH