



N 沟道增强型场效应晶体管

N-CHANNEL MOSFET

FHP230N8F3A/FHS230N8F3A/FHA230N8F3A


主要参数 MAIN CHARACTERISTICS

ID	230 A
VDSS	85 V
Rdson-typ (@Vgs=10V)	2.8 mΩ
Qg-typ	138.3 nC

用途 APPLICATIONS

电机驱动	Motor Drive
电池管理系统(TO-263)	Battery Management System (TO-263)
UPS	Uninterruptible Power Supplies
逆变电源	Power management for inverter systems


封装形式 Package



产品特性 FEATURES

低栅极电荷	Low gate charge
低 Crss (典型值 152 pF)	Low Crss (typical 152 pF)
开关速度快	Fast switching
100%经过雪崩测试	100% avalanche tested
100%经过热阻测试	100% DVDS tested
100%经过 Rg 测试	100% Rg tested
高抗 dv/dt 能力	Improved dv/dt capability
SGT 工艺	SGT technology
RoHS 产品	RoHS product

等效电路 Equivalent Circuit



绝对最大额定值 ABSOLUTE RATINGS (Tc=25℃)

项目 Parameter	符号 Symbol	数值 Value		单位 Unit
		FHP/S230N8F3A	FHA230N8F3A	
最高漏极-源极直流电压 Drain-Source Voltage	VDS	85		V
连续漏极电流* Drain Current -continuous *	ID (Tc=25℃) (Silicon Limited)	230		
	ID(Tc=25℃) (Package Limited)	180		A
	ID (Tc=100℃) (Silicon Limited)	150		A
最大脉冲漏极电流 (注 1) Drain Current – pulse (note 1)	IDM	920		A
最高栅源电压 Gate-Source Voltage	VGS	±20		V
单脉冲雪崩能量 (注 2) Single Pulsed Avalanche Energy (note 2)	EAS	648		mJ
雪崩电流 (注 1) Avalanche Current (note 1)	IAR	36		A
重复雪崩能量 (注 1) Repetitive Avalanche Current (note 1)	EAR	100		mJ
二极管反向恢复最大电压变化速率 (注 3) Peak Diode Recovery dv/dt (note 3)	dv/dt	5.0		V/ns
耗散功率 Power Dissipation	Pd (TC=25℃)	250	403	W
	-Derate above 25℃	2.0	3.60	W/℃
最高结温及存储温度 Operating and Storage Temperature Range	TJ, TSTG	150, -55 to 150		℃
引线最高焊接温度 Maximum Lead Temperature for Soldering Purposes	TL	260		℃

*漏极电流由最高结温限制

*Drain current limited by maximum junction temperature

电特性 ELECTRICAL CHARACTERISTICS

项目 Parameter	符号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单位 Units
关态特性 Off –Characteristics						
漏－源击穿电压 Drain-Source Voltage	BV _{DSS}	I _D =250μA, V _{GS} =0V	85	-	-	V
击穿电压温度特性 Breakdown Voltage Temperature Coefficient	ΔBV _{DSS} /Δ T _J	I _D =250μA, referenced to 25℃	-	0.08	-	V/℃
零栅压下漏极漏电流 Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =85V,V _{GS} =0V, T _C =25℃	-	-	1	μA
		V _{DS} =68V, T _C =125℃	-	-	100	μA
栅极体漏电流 Gate-body leakage current	I _{GSS} (F/R)	V _{DS} =0V, V _{GS} =±20V	-	-	±100	nA
通态特性 On-Characteristics						
阈值电压 Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =250μA	2.0	-	4.0	V
静态导通电阻 Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} =10V , I _D =50A	-	2.8	3.2	mΩ
正向跨导 Forward Transconductance	g _{fs}	V _{DS} = 5V, I _D =50A (note 4)	-	175	-	S
动态特性 Dynamic Characteristics						
栅极电阻 Gate resistance	R _g	f=1.0MHz,V _{DS} OPEN	-	1.4	-	Ω
输入电容 Input capacitance	C _{iss}	V _{DS} =42.5V, V _{GS} =0V, f=1.0MHz	-	8237	-	pF
输出电容 Output capacitance	C _{oss}		-	1549	-	
反向传输电容 Reverse transfer capacitance	C _{rss}		-	152	-	
开关特性 Switching Characteristics						
延迟时间 Turn-On delay time	t _{d(on)}	V _{DS} =42.5V, I _D =50A, R _G =3Ω V _{GS} =10V (note 4, 5)	-	32	-	ns
上升时间 Turn-On rise time	t _r		-	115	-	ns
延迟时间 Turn-Off delay time	t _{d(off)}		-	93	-	ns
下降时间 Turn-Off Fall time	t _f		-	140	-	ns
栅极电荷总量 Total Gate Charge	Q _g	V _{DS} =42.5V , I _D =50A , V _{GS} =10V (note 4, 5)	-	138.3	-	nC
栅－源电荷 Gate-Source charge	Q _{gs}		-	39.5	-	nC
栅－漏电荷 Gate-Drain charge	Q _{gd}		-	36.8	-	nC
漏－源二极管特性及最大额定值 Drain-Source Diode Characteristics and Maximum Ratings						
正向最大连续电流 Maximum Continuous Drain -Source Diode Forward Current	I _S		-	-	230	A
正向最大脉冲电流 Maximum Pulsed Drain-Source Diode Forward Current	I _{SM}		-	-	920	A
正向压降 Drain-Source Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _S =50A	-	-	1.2	V
反向恢复时间 Reverse recovery time	t _{rr}	V _{GS} =0V, I _S =50A ,dI _F /dt=100A/μs (note 4)	-	80	-	ns
反向恢复电荷 Reverse recovery charge	Q _{rr}		-	196	-	nC

热特性 THERMAL CHARACTERISTIC

项目 Parameter	符号 Symbol	FHP/S230N8F3A	FHA230N8F3A	单位 Unit
结到管壳的热阻 Thermal Resistance, Junction to Case	Rth(j-c)	0.5	0.31	℃/W
结到环境的热阻 Thermal Resistance, Junction to Ambient	Rth(j-A)	62.5	40	℃/W

注释:

- 1: 脉冲宽度由最高结温限制
- 2: L=1mH, IAS=36A, VDD=50V, RG=25 Ω,起始结温 TJ=25℃
- 3: ISD ≤230A,di/dt ≤100A/μs,VDD≤BV_{DSS},起始结温 TJ=25℃
- 4: 脉冲测试: 脉冲宽度 ≤300μs,占空比≤2%
- 5: 基本与工作温度无关

Notes:

- 1: Pulse width limited by maximum junction temperature
- 2: L=1mH, IAS=36A, VDD=50V, RG=25 Ω ,Start TJ=25℃;
- 3: ISD ≤230A,di/dt ≤100A/μs,VDD≤BV_{DSS}, Starting TJ=25℃
- 4: Pulse Test: Pulse Width ≤300μs,Duty Cycle≤2%
- 5: Essentially independent of operating temperature

特性曲线

(ELECTRICAL CHARACTERISTICS (curves))

Figure 1. Safe Operating Area




Figure 2. Maximum Power Dissipation vs Case Temperature




Figure 3. Maximum Continuous Drain Current vs Case Temperature




Figure 4. Typical Output Characteristics













Figure 5. Transient Thermal Impedance







Test Circuit & Waveform



Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms






Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms




印记 Marking:



外形尺寸:

Package Dimension:

TO-220




(Unit: mm)

外形尺寸:

Package Dimension:

TO-263




标注	尺寸(mm)
E	9.88±0.10
E1	7.40±0.20
E2	9.90±0.15
L	15.20±0.25
L1	1.30±0.15
L2	1.60±0.10
L3	13.00±0.20
L4	10.40±0.15
L5	2.60±0.15
L6	4.80±0.20
b	0.80±0.07
b1	1.27±0.07
b2	0.05±0.07
C	4.48±0.10
C1	1.30±0.07
C2	0.50±0.07
C3	2.40±0.06
C4	0.10±0.08
C5	0.10±0.08
D	9.20±0.10
D1	8.00±0.10
D2	8.00±0.10
R	0.50±0.10
θ1	15° ±2°
θ2	3° ±2°
θ3	3° ±2°
θ4	3° ±2°
θ5	3° ±2°
θ6	0° ~6°
θ7	13° ±2°
e	5.08±0.10
DIA	宽 1.50±0.10 深 0.30±0.15

外形尺寸:

Package Dimension:

TO-3PN



(Units: mm)