

FEATURES

- * Ideal for surface mount applications
- * Easy pick and place
- * Built-in strain relief
- * Low forward voltage drop

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Metallurgically bonded construction
- * Polarity: Color band denotes cathode end
- * Mounting position: Any
- * Weight: 0.21 grams




VOLTAGE RANGE

60 Volts

CURRENT

5.0 Amperes

DO-214AB(SMC)



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25 C ambient temperature unless otherwise specified .

Single phase half wave, 60Hz, resistive or inductive load .

For capacitive load, derate current by 20% .

TYPE NUMBER	SS56L	UNITS
Maximum Recurrent Peak Reverse Voltage	60	V
Maximum RMS Voltage	42	V
Maximum DC Blocking Voltage	60	V
Maximum Average Forward Rectified Current		
See Fig . 1	5.0	A
Peak Forward Surge Current , 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	120	A
Maximum Instantaneous Forward Voltage at 5 0A	0 55	V
Maximum DC Reverse Current Ta=25 C	0.15	mA
at Rated DC Blocking Voltage Ta=125 C	30	mA
Typical Junction Capacitance (Note1)	370	pF
Typical Thermal Resistance R JA (Note 2)	55	C/W
Operating Temperature Range Tj	-55 —+125	"C
Storage Temperature Range Tstg	-55 —+150	"C

NOTES:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. unit mounted on PC board with 5.0mm×5. 0 mm (0.013 mm thick)copper pads as heat sink

RATING AND VCHARACTERISTIC CURVES (SS56L)

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

