



PRODUCT DATA SHEET



To learn more about JGSEMI, please visit our website at



Datasheet



Resources




Samples

Please note: Please check the JINGAO Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.jg-semi.cn. Please email any questions regarding the system integration to JINGAO_questions@jgsemi.com.

■ Features

- Small plastic SMD package.
- High switching speed: max.4 ns.
- Repetitive peak forward current: max.450 mA.



■ Absolute Maximum Ratings Ta = 25°C


Parameter	Symbol	Rating	Unit
Repetitive peak reverse voltage	V _{RRM}	85	V
Continuous reverse voltage	V _R	75	V
Continuous forward current(single diode loaded *) (double diode loaded *)	I _F	215 125	mA
Repetitive peak forward current	I _{FRM}	450	mA
Non-repetitive peak forward current T _j =25 °C t=1 μs	I _{FSM}	4	A
t=1ms		1	
t=1s		0.5	
power dissipation *	P _D	250	mW
Thermal resistance from junction to tie-point	R _{th j-tp}	360	K/W
Thermal resistance from junction to ambient *	R _{th j-a}	500	K/W
Junction Temperature	T _j	150	°C
Storage Temperature Range	T _{stg}	-65 to +150	°C

* Device mounted on an FR4 printed-circuit board.

■ Electrical Characteristics Ta = 25°C


Parameter	Symbol	Test conditions	Max	Unit
Forward voltage	V _F	I _F =1 mA	715	mV
		I _F =10 mA	855	mV
		I _F =50 mA	1	V
		I _F =150 mA	1.25	V
Reverse current	I _R	V _R =75 V	1	μ A
		V _R =25 V; T _j = 150 °C	30	
		V _R =75 V; T _j = 150 °C	50	
Diode capacitance	C _d	V _R =0 V, f= 1 MHz	1.5	pF
Reverse recovery time	t _{rr}	when switched from I _F = 10 mA to I _R =10mA; R _L =100 Ω ; measured at I _R = 1mA	4	nS
Forward recovery voltage	V _{fr}	I _F = 10 mA, t _r = 20 ns	1.75	V

■ Typical Characteristics




Device mounted on an FR4 printed-circuit board.

Fig.2 Maximum permissible continuous forward current as a function of ambient temperature.



- (1) $T_j = 150$ °C; typical values.
- (2) $T_j = 25$ °C; typical values.
- (3) $T_j = 25$ °C; maximum values.

Fig.3 Forward current as a function of forward voltage.



Based on square wave currents.
 $T_j = 25$ °C prior to surge.

Fig.4 Maximum permissible non-repetitive peak forward current as a function of pulse duration.





Fig.5 Reverse current as a function of junction temperature.



$f = 1 \text{ MHz}$; $T_j = 25 \text{ }^{\circ}\text{C}$.

Fig.6 Diode capacitance as a function of reverse voltage; typical values.

Attention

1, Any and all JGSEMI products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical or material damage. Consult with your JGSEMI representative nearest you before using any JGSEMI products described or contained herein in such applications.

2, JGSEMI assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all JGSEMI products described or contained herein.

3, Specifications of any and all JGSEMI products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

4, In the event that any or all JGSEMI products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

5, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of JGSEMI Semiconductor CO., LTD.

6, Any and all information described or contained herein are subject to change without notice due to product technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the JGSEMI product that you intend to use.